

RHINO FLEX-WING APPLICATION GUIDE

Applications	APEX SERIES	EPIC SERIES	ICON SERIES
Clearing brush up to 4" in diameter		✓	
Clearing brush up to 5" in diameter			✓
Commercial mowing		✓	✓
Farm use	✓	✓	
General mowing	✓	✓	
Heavy-duty agricultural use		✓	✓
Industrial mowing		✓	✓
Pasture maintenance	✓	✓	
Right-of-way mowing		✓	✓
Roadside mowing	✓	✓	
Shredding crops		✓	
Shredding stalks	✓	✓	

Specifications	APEX 3150	EPIC 4150	EPIC 4155	ICON 5150
Cutting Width	180"	180"	180"	180"
Transport Width*	96"	96"	96"	96"
Overall Width*	187"	187"	187"	187"
Overall Length*	176"	183"	183"	183"
Cutting Height*	2"-14"	2"-14"	2"-14"	2"-14"
Self-Leveling Height Adjustment	Hydraulic Cylinder	Hydraulic Cylinder	Hydraulic Cylinder	Hydraulic Cylinder
Jack Stand	Standard	Standard	Standard	Standard
Hitch	Pull	Pull	Pull	Pull
Blade Carrier (Patent Pending)	Cast Dog-Bone Pan	Cast Dog-Bone Pan	Cast Dog-Bone Pan	Cast Dog-Bone Pan
Blades	1/2" x 4" Parallel Lift	1/2" x 4" Parallel Lift	1/2" x 4" Parallel Lift	1/2" x 5" Parallel Lift
Blade Overlap	6"	6"	6"	6"
PTO Horsepower Required	50 HP	60 HP	60 HP	70 HP
Gearbox Rating**	Divider	160 HP	250 HP	250 HP
	Center & Wing	130 HP	225 HP	225 HP
Output Shaft Diameter	2"	3"	3"	3"
Blade Tip Speed	Center 540 RPM	14,861 FPM	16,286 FPM	16,286 FPM
	Center 1000 RPM	15,570 FPM	16,380 FPM	16,380 FPM
	Wing 540 RPM	14,861 FPM	16,422 FPM	16,422 FPM
	Wing 1000 RPM	15,776 FPM	15,983 FPM	15,983 FPM
Cutting Capacity (Diameter)	3"	4"	4 1/2"	5"
Driveline Size	Main	Cat 4 CV	Cat 5 CV	Lube 4 Life Cat 5 CV
	Wing	Cat 4	Cat 4	Cat 5
Driveline Protection	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch
Deck Thickness	10 Ga	7 Ga	7 Ga	1/4"
Side Skirt	1/4"	1/4"	1/4"	1/4"
Tires & Wheels	4 Options	3 Options	3 Options	3 Options
Wing Lift Hydraulics	Standard	Standard	Standard	Standard
Wing Flex (Degrees)	90 Up / 25 Down	90 Up / 25 Down	90 Up / 25 Down	90 Up / 25 Down
Safety Tow Chain	Standard	Standard	Standard	Standard
LED Light Kit	Standard	Standard	Standard	Standard
Safety Deflectors	Rubber Deflectors or Chain Guard	Chain Guard	Chain Guard	Chain Guard

*Dependent on tire size

**Gearbox rating based on field performance

1020 S. Sangamon Ave. • Gibson City, IL 60936 TEL: 800-221-2855 OPTION 3 •

FAX: 877-408-3298

WWW.RHINOAG.COM

MEMBER OF THE
ALAMO GROUP
ALWAYS ON THE CUTTING EDGE...

FW-0815-OSP

FLEX-WING ROTARY CUTTERS



WE CAN'T KEEP THIS INNOVATION

CAGED

WWW.RHINOAG.COM

RHINO FLEX-WING NEW FEATURES



THE NEW RHINO FLEX-WING HAS BEEN UNLEASHED

OUR FLEX-WING CUTTERS
ARE DESIGNED FOR
PERFORMANCE,
RELIABILITY,
AND VALUE.



1 UNIQUE BLADE PAN CARRIER
Strong and durable stump jumper.



2 LED LIGHT KIT
State of the art LED's are incorporated into a sleek highly durable housing that will provide years of trouble free protection and safety.



3 PIVOT HITCH
Unique locking clevis device for ease of hooking up.



4 SMOOTH DOME DECK
Less clutter, easy to clean with larger cutting chamber. Three sleeker, durable deck styles available: Apex, Epic, and Icon.



5 INDEPENDENT SUSPENSION
Simple, no moving parts.



6 SAFETY COVER
Quick access for easy maintenance.

RHINO FLEX-WING SEVEN MODELS TO CHOOSE FROM

APEX

Apex Deck Style
Deck thickness 10 Ga

3100

MEDIUM-DUTY
OFFSET

126" CUTTING
WIDTH

3150

MEDIUM-DUTY

180" CUTTING
WIDTH

All models come with a 6-year gearbox warranty, 2-year warranty on the seals, and 2-year limited driveline warranty.

EPIC

Epic Deck Style
Deck thickness 7 Ga

4105

PRO OFFSET
HEAVY-DUTY

126" CUTTING
WIDTH

4150

AG
HEAVY-DUTY

180" CUTTING
WIDTH

4155

PRO
HEAVY-DUTY

180" CUTTING
WIDTH

All models come with a 6-year gearbox warranty, 2-year warranty on the seals, and 2-year limited driveline warranty.

ICON

Icon Deck Style
Deck thickness 1/4"

5100

HEAVY-DUTY
OFFSET

126" CUTTING
WIDTH

5150

SUPER-DUTY

180" CUTTING
WIDTH

All models come with a 6-year gearbox warranty, 2-year warranty on the seals, and 2-year limited driveline warranty.

AND WITH 50 YEARS EXPERIENCE,
WE KNOW HOW TO MAKE THEM
DURABLE ENOUGH FOR ANY USE.