



It's lightweight, but not to be taken lightly.

Please resist the urge to underestimate our lightweight flexwing rotary cutter. Its innovative design is purpose-built for smaller, more fuel-efficient tractors, so you'll save money every time you have to mow. But since you'll never sacrifice the performance you need to cut weeds and light brush up to 1.5 inches in diameter, you'll efficiently make short work of pasture brush control, waterway maintenance, and municipal vegetation management.

INNOVATIVE DESIGN AND TECHNOLOGY



DEEP, 10-INCH SIDE FRAME AND SLOPED DECK for greater material capacity and more productive cutting.



SIMPLE SAFETY LOCK secures deck for safe, easy transporting.

LOW-HP MODEL

FLEXWING ROTARY CUTTER

FEATURES

Tongue weight under 900 lbs.

Full-length, 24-inch replaceable side skids feature a durable, large wear surface and formed angle to prevent scalping

Multiple wheel options: laminated solid tires, used aircraft tires or foam-filled aircraft tires

Dual-wheels available on wings and center for extra flotation



STANDARD DUTY

MODEL	YRC144
Main Drivelive	Cat 4
Wing Driveline	Cat 3
Tractor Hitch	Swivel Clevis
Cutting Swath (in.)	144
Cutting Height (in.)	2-12
Cutting Capacity Diameter (in.)	1-1.5
Side Frame Depth (in.)	10
Tractor PTO (RPM)	540
Deck Thickness	12 guage
Hinges/Hinge Rod Diameter (in.)	1
Weight (lbs)	2,450
Vertical Shaft Size (in.)	2
Splitter/Spindle Gearbox HP	160 / 90
Blade Thickness (in.)	0.5
Blade Width (in.)	4
Blade Type	Blade bolt, Hi-tilt
Blade Overlap (in.)	6
Hydraulics Wing Flex	90° up., 22° down
Suspension	Spring on center
Wheel Type Options	Laminated, used aircraft, foam-filled aircraft
Shielding	Standard chain shielding
Gearbox Warranty (Limited)	6 Years

@2016 Vanmar America Corporation VT16-40