



SINGLE-SPINDLE **ROTARY CUTTERS**

FEATURES

Ideal for tractors 15 – 50 hp

3-point hitch: Limited CAT 1
& CAT 1

Quick change pins

3-year limited gearbox
warranty

Quickly cut down weeds, brush and your list of chores.


Whether you're clearing brush along miles of fence line, maintaining a roadway or just keeping weeds in check in an orchard or on a large property, these single-spindle rotary cutters sized for compact tractors help you make short work of anything that's growing where you don't want it to. Each features a rugged frame, a smooth, slope-top deck and quick-change blades built to easily handle the toughest conditions.

INNOVATIVE DESIGN AND TECHNOLOGY



FULL-LENGTH SKID SHOES

are a standard feature, allowing cutter to glide easily over rough terrain.



OPTIONAL CHAIN SHIELDING



Yanmar Single-Spindle Rotary Cutter Specifications

VEGETATION MANAGEMENT

MODEL	STANDARD DUTY				MEDIUM DUTY		
	YRC48	YRC60	YRC72	YRC84	YRC600	YRC720	YRC840
Tractor PTO HP (min)	15-50	25-50	30-65	35-90	30-120		40-120
Hitch Category/Type	Cat 1 / clevis				Cat 1 and 2 / clevis		
Cutting Width (in.)	48	60	72	84	60	72	84
Transport Width (in.)	53.5	65.5	72.5	89.5	67.5	79.5	91.5
Maximum Overall Length (in.)	92	104	116	128	104	116	128
Deck Length (in.)	58	70	84	96	70	84	96
Cutting Height Range (in.)	1-9				2-12		
Cutting Capacity (in.)	1.5	2		3			
Gearbox HP	65		75	90	120		
Gearbox Output Shaft Diameter (in.)	1.57			2			
Blade Tip Speed (FPM)	13,000	14,355	14,963	15,086	15,525	15,900	16,000
Deck Side Depth (in.)	9.4		9.8		12.6		
Approximate Weight* (lbs.)	498	604	828	1084	1,068	1,200	1,416
Blade Dimensions (in.)	(2) 0.38 x 3		(2) 0.5 x 3		(2) 0.5 x 4		
Blade Carrier	Oval stump jumper			Round stump jumper			
Blade Mount System	Quick change pins						
Blade Pin Diameter (in.)	1.5						
Cutting Deck Thickness	11-Gauge				10-Gauge		
Safety-Shielded Driveline	Cat 3			Cat 4			
Driveline Protection	Slip-clutch or shear-pin			Slip-clutch			
Tractor PTO Speed (RPM)	540						
Quick Hitch Compatible	Yes						
Cutting Area Shielding	Chain shielding optional						

*Weight without chain shielding

Yanmar has a corporate policy of continuous product improvement and development; therefore, data, specifications, and warranty are subject to change without any advance notice. There may be differences between the specifications and illustrations contained in this publication and the actual equipment. Equipment components produced by other manufacturers may be shown in photographs in this publication for the purpose of illustration only and is not intended as an endorsement of that particular equipment or its suitability. Inspect equipment before using it and be sure it is operating properly. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manuals. Before operating a machine, read, understand, and follow all instructions in the manual and on the machine. Yanmar disclaims all representations, express or implied, or any liability from the use of this publication.